

PRODUCT SPECIFICATIONS SHEET

Model: Jazzy Air® MED

Document Information: INFINF4559/Rev B/November 2023

Weight Capacity	300 lbs. (136 kg) 21 stone 6 lbs.
Maximum Speed ¹	Up to 3.71 mph (5.97 km/h)
Ground Clearance ²	0.98 in. (25 mm) at Motor Bracket
Turning Radius ²	24.41 in. (620 mm)
Overall Size ^{2, 6}	Length: 41.54 in. (1055 mm) Width: 23.25 in. (590 mm)
Drive Wheels	10 in. (254 mm), Flat free
Caster Wheels	6 in. (152 mm), Flat free
Suspension	Active-Trac® with Mid-Wheel 6 Technology
Range ^{1, 4}	Up to 13 miles (20.92 km) at 300 lbs. (136.1 kg) 21 stone 6 lbs. Up to 14.1 miles (22.69 km) at 220 lbs. (99.8 kg) 15 stone 10 lbs.
Component Weights ⁵	Complete Assembly (without batteries): 197.2 lbs. (89.45 kg) Batteries: 22.2 lbs. (10.1 kg) each
Drivetrain	Two motor, mid-wheel-6 drive®
Brakes	“Intelligent Braking” electronic regenerative, disc park brake
Batteries ³	Two 12-volt, sealed lead-acid, non-spillable deep-cycle U-1 batteries
Battery Charger	5 amp, off-board
Freewheel Operational Force	Less than 60 N
Drive Control Operational Force	Less than 5 N
Maximum Rated Slope	6° (10.5%)
Maximum Obstacle Climbing Ability (Ascending and Descending)	1.57 in. (40 mm)
Measured Sound Level (A-weighted)	Less than 65 dB

¹ Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM, Gel-Cell, Lithium-Ion, or Hybrid Gel (Hybrid Gel is defined as Nano Silica Gel Electrolyte with High Quality Glass Mat Separators) type required. See III. “Batteries and Charging.”

⁴ Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA and ISO 7176 Series standards. All specifications subject to change without notice.

